

6.3mm Thermal Plastic Hose

PVC Single-layer polyester braided pressure washer hose

PHP-5632M-8
Hose ID: 6.3mm-1/4"
Max Pressure: 3200psi/220bar
Fitting: M22 Swivel
Length: 8M



6.3/8mm Single Steel Braided Hose

Rubberized fabric single layer steel braided pressure washer hose

SHP-5632Q-10 **SHP-5832Q-10**
Hose ID: 6.3mm-1/4"
Max: 3200psi/220bar
Fitting: 3/8" OD
Length: 10.15, 20M



6.3/8mm Single Steel Braided Smooth Hose

Smooth finish single layer steel braided pressure washer hose

SHP5-5632Q-10 **SHP5-5832Q-10**
Hose ID: 6.3mm-1/4"
Max: 3200psi/220bar
Fitting: 3/8" OD
Length: 10.15, 20M



SHP5-5836-10
Hose ID: 8mm-5/16"
Max: 3600psi/25bar
Fitting: 3/8" OD
Length: 10.15, 20M

Steel Braided Hydraulic Hose

Rubberized fabric triplex layer steel braided hydraulic hose

SHP-T10100T
Hose ID: 10mm-3/8"
Max: 1000psi/70bar
Fitting: M8x1.5 Female
Length: 10, 15, 20M



Single Wire Braided Ultra Wear-resistant Jetting Hose

Super wear-resistant single layer steel wire braided pressure washer hose

SHPW-5632T **SHPW-5831T**
Hose ID: 6.3mm-1/4"
Max: 3500psi/25bar
Fitting: 1/4" Male
Length: 30, 60M



SHPW-5126T **SHPW-5123T**
Hose ID: 10mm-3/8"
Max: 2600psi/180bar
Fitting: 3/8" Male
Length: 30, 60M

7mm Thermal Plastic Hose

PVC Single-layer polyester braided pressure washer hose

PHP-5732Q-10
Hose ID: 7mm-9/32"
Max Pressure: 3200psi/220bar
Fitting: 3/8" Quick Connector
Length: 10M



8/10mm Dual Steel Braided Hose

Rubberized fabric dual layer steel braided pressure washer hose

SHP-0843Q-10 **SHP-01043Q-10**
Hose ID: 8mm-5/16"
Max: 4350psi/300bar
Fitting: 3/8" OD
Length: 10.15, 20M



8/10mm Dual Steel Braided Smooth Hose

Smooth finish dual layer steel braided pressure washer hose

SHP5-0843Q-10 **SHP5-01043Q-10**
Hose ID: 8mm-5/16"
Max: 4350psi/300bar
Fitting: 3/8" OD
Length: 10.15, 20M



SHP5-01050Q-10
Hose ID: 10mm-3/8"
Max: 5000psi/345bar
Fitting: 3/8" OD
Length: 10.15, 20M

Steel Braided Hot Water Pressure Hose

Rubberized fabric steel braided hot water pressure washer hose

SHPH-5832T
Hose ID: 8mm-5/16"
Max: 3200psi/220bar
Fitting: 3/8" Male
Length: 10, 15, 20M



Dual Wire Braided Ultra Wear-resistant Jetting Hose

Super wear-resistant dual layer steel braided pressure washer hose

SHPW-0658T **SHPW-0850T**
Hose ID: 6.3mm-1/4"
Max: 5800psi/400bar
Fitting: 1/4" Male
Length: 30, 60M



SHPW-01048T **SHPW-51240T**
Hose ID: 10mm-3/8"
Max: 4800psi/330bar
Fitting: 1/2" Male
Length: 30, 60M

Retracting Hose Reel

Spring Loaded Auto Retractable Hose Reel

Thickened steel plate, double support arm can ensure the reliability and stability of use. Including base can be installed as upward, downward or vertically. The reinforced spring can be rolled up to 19 meters of high pressure hose, thickened 8-tooth chuck to ensure reliable and wear resistance. Up and down, left and right guide roller ensures the correct guidance when the hose is automatically retract. The end of the high pressure hose contains a fiber. Stainless steel rotary shaft with dual bearing fixed structure rotary joint, wear resistant and resistant to high pressure, including 1 meter short connector hose thread size can be option.



HPHR-BR3D

Base Mounting Pressure Hose Reel

3/8" x 30M fixed base mounting high pressure hose reel

Direct hand crank rewind, heavy duty steel construction with black durable powder coating, full flow swivel brass joint body with stainless steel shaft. Fixed flat mounting base, provide with 1 meter connection hose, fitting type can be order.
Max Temp: 90°C/194°F
Max Pressure: 3600psi/248bar
Inlet: 3/8" Male-M22 Swivel
Outlet: 3/8" Female
Hose Capacity: 3/8" x 30M



HPHR-WRGO

Wheeled Frame Portable Pressure Hose Reel

3/8" x 60/90M wheeled frame high pressure hose reel

Steel construction, powder coating, bearing-loaded stainless steel swivel joint, on-off inlet cock. Hand rewinding with locking. Hand portable, with rubber feet and 7" wheel for easy wheel moving and stand on the floor.
Max Temp: 60°C/140°F
Max Pressure: 3600psi/248bar
Inlet Fitting: 3/8" OD plug
Outlet Fitting: 3/8" Female
Hose Capacity: 3/8" x 60M, 90M for option



HPHR-EP3D

Easy Portable High Pressure Hose Reel

1/4" x 30M easy portable high pressure hose reel

All steel construction with powder coating, full flow swivel brass joint body with stainless steel shaft. Easy hand rewinding and portable, with rubber feet can stand on the floor. Features the quick locking construction can quick install on the pressure washer.
Max Temp: 60°C/140°F
Max Pressure: 3600psi/248bar
Inlet: 3/8" Male
Outlet: 3/8" Female
Hose Capacity: 1/4" x 30M



HPHR-BP3D

Base Pivoting Mounting Pressure Hose Reel

3/8" x 30M fixed base pivoting high pressure hose reel

Direct hand crank rewind, heavy duty steel construction with black durable powder coating, full flow swivel brass joint body with stainless steel shaft. Provide with mounting base, 360° rotating with locking mechanism, one meter connection hose, fitting type can be order.
Max Temp: 90°C/194°F
Max Pressure: 3600psi/248bar
Inlet: 3/8" Male-M22 Swivel
Outlet: 3/8" Female
Hose Capacity: 3/8" x 30M



HPHR-SR3/8"-19

Self Retract High Pressure Hose Reel

3/8" x 19M spring loaded auto retractable High Pressure Hose Reel

Heavy duty steel construction for industrial and commercial applications, powder coating. Spring powered auto rewind. Reel can be top, up and side mounting. Features adjusting guide arm, hose stop guard, 8 position ratchet latch, solid steel axle and stainless steel flexible joint.
Max Temp: 60°C/140°F
Max Pressure: 3600psi/248bar
Inlet: 3/8" Male-M22 Swivel
Outlet: 3/8" Female
Hose Capacity: 3/8" x 19M



HPHR-QR6D

QR Portable High Pressure Hose Reel

3/8" x 60/90M Portable High Pressure Hose Reel

Heavy duty steel construction, black powder coating, bearing loaded, durable stainless steel swivel joint. Hand rewinding with locking mechanism. Hand portable, with rubber feet can stand on the floor. Features the quick locking construction can quick install on the pressure washer.
Max Temp: 60°C/140°F
Max Pressure: 3600psi/248bar
Inlet: 3/8" Male
Outlet: 3/8" Female
Hose Capacity: 3/8" x 60M, 90M for option

