

WTF1-1N3/4" WTF1-1N3/4"BY

Clear View Pressure Pump In-line Water Filter

Made of brass body with the clear plastic cover and stainless steel screen. It catches debris and sediment before they enter the pump, preventing damage to the pump and prolonging its lifespan. The clear body allows for easy visual inspection to determine when cleaning is needed. It also comes with a 1/4-inch bypass port, can direct the overflow from unloader valve to water inlet and make it as internal recycle.

Max Flow: 86gpm/300gpm
 Max Pressure: 75psi/5bar
 Inlet Fitting: 1/2" Male
 Outlet Fitting: 3/4" Female, Swivel
 Bypass Port: 1/4" Female, Plug
 Screen Mesh: 40



WTF1-A13/8"

Aluminum Water Inlet Filter

Anodized aluminum body plus with the clear cap and stainless steel screen. Inlet size available for 1/2" Male or 3/4" Male, and thread type BSP or NPT. Outlet size available for 1/2" Female or 3/4" Female swivel nut, and thread type BSP or NPT. Dual 1/4" female bypass inlet port, fit with plug.

Max Temp. 90°C/194°F
 Hose Fitting: 15mm and 20mm
 Screen Mesh: 80



WTF1-G03/4"

Standard Garden Hose Water Filter

Standard garden hose connection, easily attaches to your pressure washer or home spigot. Clear PC bowl plus with stainless steel large screen, easy to clean up without take off the pipe line. Reinforced with metal garden hose fitting 3/4" Male x Female swivel, thread available for BSP or NPT.

Max Temp. 90°C/194°F
 Screen Mesh: 40



WTF1-P13/4"

Pipe Line Water Filter

PA(Nylon) material filter body, molded with brass female connecting collar, top mounting hole and air pressure release cap. Bottom wind tighten cap. PV material clear bowl, plastic framed screen.

For easy check, clean and changing.
 Max Temp. 60°C/140°F
 Screen Mesh: 80
 Fitting: PC 3/4"-3/4" Female
 PL 1"-1" Female
 Size(LXWH): P13/4" 14.5x13x23cm
 PL1" 14.5x13x22cm



WTF1-CP1-M80 WTF1-CP2-M80

Plastic Cup Water Inlet Filter

Cup type in-line water inlet filter, clear PC bowl for easy watch and easy to clean up the screen. Fitting size 3/4" and thread available for BSP and NPT.

Max Temp. 60°C/140°F
 Screen mesh: 80



WTF1-BM15/20

Step Sized Brass Drum Type Pickup Suction Water Filter

Two ends made of brass with a stepped tail barb from 15mm to 20mm. It comes with a stainless steel screen, and blue nylon filter frame. It is easy to use and install by simply pushing the hose into the hook. The filter works perfectly to prevent sand, particles, or debris from entering the pump.

Max Temp. 60°C/140°F
 Hose Fitting: 15mm and 20mm
 Screen Mesh: 40



WTF1-D5

Double Strainer Integrate Water Inlet Filter

It consists of a large flow bottom filter and a top in-line filter with tail barb size 16mm. The filters are made of plastic body and stainless steel screen. The bottom filter constructed with three legs and can stand on the bottom of the water tank to prevent the suction of bottom sediments. It is easy to use and install by simply pushing the hose into the hook. The filter works perfectly to prevent sand, particles, or debris from entering the pump.

Max Temp. 60°C/140°F
 Hose Fitting: Barid 16mm, or option
 Screen Mesh: Bottom 40, Top 80



WTF1-H12"

2" High Flow Water Inlet Filter

Aluminum alloy casing body with top mounting holes, PC clear bowl bottom installed with copper discharge 1/2" ball cock. Stainless steel strainer tube.

Max Temp. 60°C/140°F
 Max Flow: 52.86gpm/200gpm
 Max Pressure: 87Psi/6bar
 Inlet/Outlet Fitting: Flange Bolt Circle 75mm
 Size (LXWH): 17.3x16x44.5cm



1/4" High Pressure Quick Disconnect Fitting (Max 4500psi)

CODE	TYPE	INLET	THREAD	MATERIAL
A1	QD Socket	1/4" Male	NPT or BSP	Brass
A2	QD Socket	1/4" Female	NPT or BSP	Brass
A3	QD Plug	1/4" Female	NPT or BSP	Steel, plated
A4	QD Plug	1/4" Male	NPT or BSP	Steel, plated
A5	QD Plug	1/4" Male	NPT or BSP	Stainless Steel
A6	QD Socket	1/4" Female	NPT or BSP	Stainless Steel



3/8" High Pressure Quick Disconnect Fitting (Max 4500psi)

CODE	TYPE	INLET	THREAD	MATERIAL
B1	QD Socket	3/8" Female	NPT or BSP	Brass
B2	QD Socket	3/8" Male	NPT or BSP	Brass
B3	QD Socket	M22x1.5		Brass
B4	QD Plug	3/8" Female	NPT or BSP	Steel, plated
B5	QD Plug	3/8" Male	NPT or BSP	Steel, plated
B6	QD Plug	M22x1.5		Steel, plated
B7	QD Plug	3/8" Female	NPT or BSP	Stainless Steel
B8	QD Plug	3/8" Male	NPT or BSP	Stainless Steel
B9	QD Socket	3/8" Female	NPT or BSP	Stainless Steel
B10	QD Plug (Anti-Dts)	3/8" Male	NPT or BSP	Stainless Steel
B11	QD Socket (Anti-Dts)	3/8" Female	NPT or BSP	Stainless Steel



M22 Swivel Nut High Pressure Fitting (Max 4500psi)

CODE	TYPE	INLET	THREAD	MATERIAL
C1	M22 Swivel Nut	1/4" Female	NPT or BSP	Brass
C2	M22 Swivel Nut	1/4" QD plug	NPT or BSP	Steel, plated
C3	M22 Swivel Nut	1/4" Male	NPT or BSP	Brass
C4	M22 Swivel Nut	3/8" QD Socket	NPT or BSP	Brass
C5	M22 Swivel Nut	3/8" QD plug	NPT or BSP	Steel, plated
C6	M22 Swivel Nut	3/8" Female	NPT or BSP	Brass
C7	M22 Swivel Nut	3/8" Male	NPT or BSP	Brass
C8	M22 Swivel Nut	M22x1.5		Brass
C9	M22 Swivel Nut	M22x1.5		Brass



High Pressure Changing Fitting, Male to Male (Max 4500psi)

CODE	MALE	MALE	THREAD	MATERIAL
D1	1/4"	1/4"	NPT or BSP	Brass
D2	1/4"	3/8"	NPT or BSP	Brass
D3	1/4"	M22	NPT or BSP	Brass
D4	3/8"	3/8"	NPT or BSP	Brass
D5	3/8"	M22	NPT or BSP	Brass
D6	3/8"	1/2"	NPT or BSP	Brass
D7	M22	M22x1.5		Brass
D8	1/2"	3/4"	NPT or BSP	Brass

