

DAC SERIES

V **VERSION**
 Vertical Engine Direct Drive
HOLLOW SHAFT
BORE 22.23mm
KEY 4.78mm

APPLICATIONS. Consult us for more



COMPONENTS

MANIFOLD Brass Forged	HOUSING Aluminum Alloy	WOBBLE PLATE Forged Steel Alloy	BEARING Thrust Bearing	PLUNGER Coating Ceramic	PACKING U Type Dual Seal

TECHNICAL DATA

Manifold:	Brass forged	Unloader:	Integrated with manifold
Housing:	Die-cast aluminum alloy, anodized	Unloader Port:	Inlet 3/4" (BSP or NH), Outlet M22
Wobble Plate:	Forged steel alloy	Oil Bath Capacity:	120ml
Plunger:	Ceramic coating, precision grinded	Oil Type:	15W/40 Non-Detergent
Packing:	U type, high-low dual pressure packing	Water Inlet Pressure:	0-50psi/3.5bar
Bearing:	Dual thrust bearing	Max Inlet Water Temp.	≤ 50°C/122°F

MODEL	MAX FLOW		MAX PRESSURE		POWER INPUT	POWER SPEED	WEIGHT	SHIPPING SIZE
	GPM	LPM	PSI	BAR	HP	RPM	KG	CM
DAC-13071V	2.0	7.6	2400	166	6.5	3400	3.7	25x22.5x20
DAC-14067V	2.1	8.0	2600	179	6.5	3400	3.7	25x22.5x20
DAC-14071V	2.4	9.1	2600	179	6.5	3400	3.7	25x22.5x20

OVERALL DIMENSION

